# Package: multibias (via r-universe)

November 17, 2026

**Type** Package

**Title** Multiple Bias Analysis in Causal Inference

**Version** 1.7.3

**Date** 2026-04-20

**Maintainer** Paul Brendel <pcbrendel@gmail.com>

**Description** Quantify exposure-outcome causal effects with adjustment for multiple biases. The functions can simultaneously adjust for any combination of uncontrolled confounding, exposure/outcome misclassification, and selection bias. The underlying method generalizes the combination of inverse probability of selection weighting with predictive value weighting. Simultaneous multi-bias analysis can be used to enhance the validity and transparency of real-world evidence obtained from observational, longitudinal studies. Based on the work from Paul Brendel, Aracelis Torres, and Onyebuchi Arah (2023) <doi:10.1093/ije/dyad001>.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 4.2.0)

**RoxygenNote** 7.3.2

**Imports** dplyr (>= 1.1.3), lifecycle (>= 1.0.3), magrittr (>= 2.0.3), rlang (>= 1.1.1), broom (>= 1.0.5), purrr (>= 1.0.0), ggplot2 (>= 3.5.0)

**Suggests** knitr, rmarkdown, MASS, testthat (>= 3.0.0), vdiffr (>= 1.0.5)

**URL** https://github.com/pcbrendel/multibias, http://www.paulbrendel.com/multibias/

**BugReports** https://github.com/pcbrendel/multibias/issues

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**Roxygen** list(markdown = TRUE)

**Config/pak/sysreqs** libicu-dev

**Repository** https://pcbrendel.r-universe.dev

**Date/Publication** 2026-04-20 22:42:42 UTC

**RemoteUrl** https://github.com/pcbrendel/multibias

**RemoteRef** HEAD

**RemoteSha** 4b68218f5500b3b0e79b64e396c76c32e92514aa

# Contents

bias_params . . . 3
data_observed . . . 5
data_validation . . . 6
df_em . . . 7
df_em_om . . . 8
df_em_om_source . . . 8
df_em_sel . . . 9
df_em_sel_source . . . 10
df_em_source . . . 10
df_om . . . 11
df_om_sel . . . 12
df_om_sel_source . . . 12
df_om_source . . . 13
df_sel . . . 14
df_sel_source . . . 14
df_uc . . . 15
df_uc_em . . . 16
df_uc_em_sel . . . 16
df_uc_em_sel_source . . . 17
df_uc_em_source . . . 18
df_uc_om . . . 18
df_uc_om_sel . . . 19
df_uc_om_sel_source . . . 20
df_uc_om_source . . . 20
df_uc_sel . . . 21
df_uc_sel_source . . . 22
df_uc_source . . . 22
multibias_adjust . . . 23
multibias_plot . . . 26

**Index** **28**

`bias_params` *Represent bias parameters*

## Description

`bias_params` is one of two different options to represent bias assumptions for bias adjustment. The `multibias_adjust()` function will apply the assumptions from these models and use them to adjust for biases in the observed data. It takes one input, a list, where each item in the list corresponds to the necessary models for bias adjustment. See below for bias models.

For each of the following bias models, the variables are defined:

- X = True exposure
- X* = Misclassified exposure
- Y = True outcome
- Y* = Misclassified outcome
- C = Known confounder
- j = Number of known confounders
- U = Uncontrolled confounder
- S = Selection indicator

**Uncontrolled confounding** $logit(P(U = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 Y + \alpha_{2+j} C_j$

**Exposure misclassification** $logit(P(X = 1)) = \delta_0 + \delta_1 X^* + \delta_2 Y + \delta_{2+j} C_j$

**Outcome misclassification** $logit(P(Y = 1)) = \delta_0 + \delta_1 X + \delta_2 Y^* + \delta_{2+j} C_j$

**Selection bias** $logit(P(S = 1)) = \beta_0 + \beta_1 X + \beta_2 Y$

**Uncontrolled Confounding & Exposure Misclassification (Option 1)** $logit(P(U = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 Y$
$logit(P(X = 1)) = \delta_0 + \delta_1 X^* + \delta_2 Y + \delta_{2+j} C_j$

**Uncontrolled Confounding & Exposure Misclassification (Option 2)** $log(P(X = 1, U = 0)/P(X = 0, U = 0)) = \gamma_{1,0} + \gamma_{1,1} X^* + \gamma_{1,2} Y + \gamma_{1,2+j} C_j$
$log(P(X = 0, U = 1)/P(X = 0, U = 0)) = \gamma_{2,0} + \gamma_{2,1} X^* + \gamma_{2,2} Y + \gamma_{2,2+j} C_j$
$log(P(X = 1, U = 1)/P(X = 0, U = 0)) = \gamma_{3,0} + \gamma_{3,1} X^* + \gamma_{3,2} Y + \gamma_{3,2+j} C_j$

**Uncontrolled Confounding & Outcome Misclassification (Option 1)** $logit(P(U = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 Y$
$logit(P(Y = 1)) = \delta_0 + \delta_1 X + \delta_2 Y^* + \delta_{2+j} C_j$

**Uncontrolled Confounding & Outcome Misclassification (Option 2)** $log(P(U = 1, Y = 0)/P(U = 0, Y = 0)) = \gamma_{1,0} + \gamma_{1,1} X + \gamma_{1,2} Y^* + \gamma_{1,2+j} C_j$
$log(P(U = 0, Y = 1)/P(U = 0, Y = 0)) = \gamma_{2,0} + \gamma_{2,1} X + \gamma_{2,2} Y^* + \gamma_{2,2+j} C_j$
$log(P(U = 1, Y = 1)/P(U = 0, Y = 0)) = \gamma_{3,0} + \gamma_{3,1} X + \gamma_{3,2} Y^* + \gamma_{3,2+j} C_j$

**Uncontrolled Confounding & Selection Bias** $logit(P(U = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 Y + \alpha_{2+j} C_j$
$logit(P(S = 1)) = \beta_0 + \beta_1 X + \beta_2 Y$

**Exposure Misclassification & Outcome Misclassification (Option 1)** $logit(P(X = 1)) = \delta_0 + \delta_1 X^* + \delta_2 Y^* + \delta_{2+j} C_j$
$logit(P(Y = 1)) = \beta_0 + \beta_1 X + \beta_2 Y^* + \beta_{2+j} C_j$

**Exposure Misclassification & Outcome Misclassification (Option 2)** $log(P(X = 1, Y = 0)/P(X = 0, Y = 0)) = \gamma_{1,0} + \gamma_{1,1}X^* + \gamma_{1,2}Y^* + \gamma_{1,2+j}C_j$
$log(P(X = 0, Y = 1)/P(X = 0, Y = 0)) = \gamma_{2,0} + \gamma_{2,1}X^* + \gamma_{2,2}Y^* + \gamma_{2,2+j}C_j$
$log(P(X = 1, Y = 1)/P(X = 0, Y = 0)) = \gamma_{3,0} + \gamma_{3,1}X^* + \gamma_{3,2}Y^* + \gamma_{3,2+j}C_j$

**Exposure Misclassification & Selection Bias** $logit(P(X = 1)) = \delta_0 + \delta_1 X^* + \delta_2 Y + \delta_{2+j}C_j$
$logit(P(S = 1)) = \beta_0 + \beta_1 X^* + \beta_2 Y + \beta_{2+j}C_j$

**Outcome Misclassification & Selection Bias** $logit(P(Y = 1)) = \delta_0 + \delta_1 X + \delta_2 Y^* + \delta_{2+j}C_j$
$logit(P(S = 1)) = \beta_0 + \beta_1 X + \beta_2 Y^* + \beta_{2+j}C_j$

**Uncontrolled Confounding, Exposure Misclassification, and Selection Bias (Option 1)** $logit(P(U = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 Y$
$logit(P(X = 1)) = \delta_0 + \delta_1 X^* + \delta_2 Y + \delta_{2+j}C_j$
$logit(P(S = 1)) = \beta_0 + \beta_1 X^* + \beta_2 Y + \beta_{2+j}C_j$

**Uncontrolled Confounding, Exposure Misclassification, and Selection Bias (Option 2)** $log(P(X = 1, U = 0)/P(X = 0, U = 0)) = \gamma_{1,0} + \gamma_{1,1}X^* + \gamma_{1,2}Y + \gamma_{1,2+j}C_j$
$log(P(X = 0, U = 1)/P(X = 0, U = 0)) = \gamma_{2,0} + \gamma_{2,1}X^* + \gamma_{2,2}Y + \gamma_{2,2+j}C_j$
$log(P(X = 1, U = 1)/P(X = 0, U = 0)) = \gamma_{3,0} + \gamma_{3,1}X^* + \gamma_{3,2}Y + \gamma_{3,2+j}C_j$
$logit(P(S = 1)) = \beta_0 + \beta_1 X^* + \beta_2 Y + \beta_{2+j}C_j$

**Uncontrolled Confounding, Outcome Misclassification, and Selection Bias (Option 1)** $logit(P(U = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 Y$
$logit(P(Y = 1)) = \delta_0 + \delta_1 X + \delta_2 Y^* + \delta_{2+j}C_j$
$logit(P(S = 1)) = \beta_0 + \beta_1 X + \beta_2 Y^* + \beta_{2+j}C_j$

**Uncontrolled Confounding, Outcome Misclassification, and Selection Bias (Option 2)** $log(P(U = 1, Y = 0)/P(U = 0, Y = 0)) = \gamma_{1,0} + \gamma_{1,1}X + \gamma_{1,2}Y^* + \gamma_{1,2+j}C_j$
$log(P(U = 0, Y = 1)/P(U = 0, Y = 0)) = \gamma_{2,0} + \gamma_{2,1}X + \gamma_{2,2}Y^* + \gamma_{2,2+j}C_j$
$log(P(U = 1, Y = 1)/P(U = 0, Y = 0)) = \gamma_{3,0} + \gamma_{3,1}X + \gamma_{3,2}Y^* + \gamma_{3,2+j}C_j$
$logit(P(S = 1)) = \beta_0 + \beta_1 X + \beta_2 Y^* + \beta_{2+j}C_j$

## Usage

```
bias_params(coef_list)
```

## Arguments

| | |
|---|---|
| `coef_list` | List of coefficient values from the above options of models. Each item of the list is an equation. The left side of the equation identifies the model (i.e., "u" for the model predicting the uncontrolled confounder). For the multinomial models, specify the value here based on the numerator (i.e., "x1u0", "x0u1", "x1u1" for the three multinomial models in Uncontrolled Confounding & Exposure Misclassification, Option 2) The right side of the equation is the vector of values corresponding to the model coefficients (from left to right). |

## Examples

```
list_for_uc <- list(
  u = c(-0.19, 0.61, 0.70, -0.09, 0.10, -0.15)
)

bp_uc <- bias_params(coef_list = list_for_uc)
```

```
list_for_em_om <- list(
  x1y0 = c(-2.18, 1.63, 0.23, 0.36),
  x0y1 = c(-3.17, 0.22, 1.60, 0.40),
  x1y1 = c(-4.76, 1.82, 1.83, 0.72)
)

bp_em_om <- bias_params(coef_list = list_for_em_om)
```

---

`data_observed` *Represent observed causal data*

---

## Description

`data_observed` combines the observed dataframe with specific identification of the columns corresponding to the exposure, outcome, and confounders. It is an essential input of the `multibias_adjust()` function.

## Usage

```
data_observed(data, bias, exposure, outcome, confounders = NULL)
```

## Arguments

| | |
|---|---|
| `data` | Dataframe for bias analysis. |
| `bias` | String type(s) of bias distorting the effect of the exposure on the outcome. Can choose from a subset of the following: "uc", "em", "om", "sel". These correspond to uncontrolled confounding, exposure misclassification, outcome misclassification, and selection bias, respectively. |
| `exposure` | String name of the column in `data` corresponding to the exposure variable. |
| `outcome` | String name of the column in `data` corresponding to the outcome variable. |
| `confounders` | String name(s) of the column(s) in `data` corresponding to the confounding variable(s). |

## Value

An object of class `data_observed` containing:

| | |
|---|---|
| `data` | A dataframe with the selected columns |
| `bias` | The type(s) of bias present |
| `exposure` | The name of the exposure variable |
| `outcome` | The name of the outcome variable |
| `confounders` | The name(s) of the confounder variable(s) |

## Examples

```
df <- data_observed(
  data = df_uc,
  bias = "uc",
  exposure = "X_bi",
  outcome = "Y_bi",
  confounders = c("C1", "C2", "C3")
)
```

---

`data_validation` *Represent validation causal data*

---

## Description

`data_validation` is one of two different options to represent bias assumptions for bias adjustment. It combines the validation dataframe with specific identification of the appropriate columns for bias adjustment, including: true exposure, true outcome, confounders, misclassified exposure, misclassified outcome, and selection. The purpose of validation data is to use an external data source to transport the necessary causal relationships that are missing in the observed data.

## Usage

```
data_validation(
  data,
  true_exposure,
  true_outcome,
  confounders = NULL,
  misclassified_exposure = NULL,
  misclassified_outcome = NULL,
  selection = NULL
)
```

## Arguments

| | |
|---|---|
| `data` | Dataframe of validation data |
| `true_exposure` | String name of the column in `data` corresponding to the true exposure. |
| `true_outcome` | String name of the column in `data` corresponding to the true outcome. |
| `confounders` | String name(s) of the column(s) in `data` corresponding to the confounding variable(s). |
| `misclassified_exposure` | String name of the column in `data` corresponding to the misclassified exposure. |
| `misclassified_outcome` | String name of the column in `data` corresponding to the misclassified outcome. |
| `selection` | String name of the column in `data` corresponding to the selection indicator. |

## Value

An object of class `data_validation` containing:

| | |
|---|---|
| `data` | A dataframe with the selected columns |
| `true_exposure` | The name of the true exposure variable |
| `true_outcome` | The name of the true outcome variable |
| `confounders` | The name(s) of the confounder variable(s) |
| `misclassified_exposure` | The name of the misclassified exposure variable |
| `misclassified_outcome` | The name of the misclassified outcome variable |
| `selection` | The name of the selection indicator variable |

## Examples

```
df <- data_validation(
  data = df_sel_source,
  true_exposure = "X",
  true_outcome = "Y",
  confounders = c("C1", "C2", "C3"),
  selection = "S"
)
```

---

# df_em *Simulated data with exposure misclassification*

---

## Description

Data containing one source of bias, three known confounders, and 100,000 observations. This data is obtained from `df_emc_source` by removing the column *X*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified exposure, *Xstar*, and no data on the true exposure. As seen in `df_emc_source`, the true, unbiased exposure-outcome odds ratio = 2.

## Usage

```
df_em
```

## Format

A dataframe with 100,000 rows and 5 columns:

**Xstar** misclassified exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_em_om — *Simulated data with exposure misclassification and outcome misclassification*

### Description

Data containing two sources of bias, three known confounders, and 100,000 observations. This data is obtained from `df_emc_omc_source` by removing the columns *X* and *Y*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified exposure, *Xstar*, and a misclassified outcome, *Ystar*. As seen in `df_em_om_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_em_om
```

### Format

A dataframe with 100,000 rows and 5 columns:

**Xstar** misclassified exposure, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_em_om_source — *Data source for* `df_em_om`

### Description

Data with complete information on the two sources of bias, three known confounders, and 100,000 observations. This data is used to derive `df_em_om` and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with `df_em_om`. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_em_om_source
```

### Format

A dataframe with 100,000 rows and 7 columns:

**X** true exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**Xstar** misclassified exposure, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

---

## df_em_sel *Simulated data with exposure misclassification and selection bias*

---

### Description

Data containing two sources of bias, three known confounders, and 100,000 observations. This data is obtained by sampling with replacement with probability = *S* from `df_em_sel_source` then removing the columns *X* and *S*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified exposure, *Xstar*, and missing data for those not selected into the study (*S*=0). As seen in `df_em_sel_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_em_sel
```

### Format

A dataframe with 100,000 rows and 5 columns:

**Xstar** misclassified exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_em_sel_source *Data source for* df_em_sel

### Description

Data with complete information on the two sources of bias, three known confounders, and 100,000 observations. This data is used to derive df_em_sel and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with df_em_sel. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_em_sel_source
```

### Format

A dataframe with 100,000 rows and 7 columns:

**X** true exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**Xstar** misclassified exposure, 1 = present and 0 = absent

**S** selection, 1 = selected into the study and 0 = not selected into the study

## df_em_source *Data source for* df_em

### Description

Data with complete information on one sources of bias, three known confounders, and 100,000 observations. This data is used to derive df_em and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with df_em. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_em_source
```

### Format

A dataframe with 100,000 rows and 6 columns:

**X** exposure, 1 = present and 0 = absent

**Y** true outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**Xstar** misclassified exposure, 1 = present and 0 = absent

---

## df_om *Simulated data with outcome misclassification*

---

### Description

Data containing one source of bias, three known confounders, and 100,000 observations. This data is obtained from `df_om_source` by removing the column *Y*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified outcome, *Ystar*, and no data on the true outcome. As seen in `df_om_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_om
```

### Format

A dataframe with 100,000 rows and 5 columns:

**X** exposure, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_om_sel — *Simulated data with outcome misclassification and selection bias*

### Description

Data containing two sources of bias, a known confounder, and 100,000 observations. This data is obtained by sampling with replacement with probability = *S* from `df_om_sel_source` then removing the columns *Y* and *S*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified outcome, *Ystar*, and missing data for those not selected into the study (*S*=0). As seen in `df_om_sel_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_om_sel
```

### Format

A dataframe with 100,000 rows and 5 columns:

**X** exposure, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_om_sel_source — *Data source for* `df_om_sel`

### Description

Data with complete information on the two sources of bias, a known confounder, and 100,000 observations. This data is used to derive `df_om_sel` and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with `df_om_sel`. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_om_sel_source
```

### Format

A dataframe with 100,000 rows and 7 columns:

**X** exposure, 1 = present and 0 = absent

**Y** true outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

**S** selection, 1 = selected into the study and 0 = not selected into the study

---

## df_om_source *Data source for* df_om

---

### Description

Data with complete information on one sources of bias, three known confounders, and 100,000 observations. This data is used to derive df_om and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with df_om. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_om_source
```

### Format

A dataframe with 100,000 rows and 6 columns:

**X** exposure, 1 = present and 0 = absent

**Y** true outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

## df_sel *Simulated data with selection bias*

### Description

Data containing one source of bias, three known confounders, and 100,000 observations. This data is obtained by sampling with replacement with probability = *S* from `df_sel_source` then removing the *S* column. The resulting data corresponds to what a researcher would see in the real-world: missing data for those not selected into the study (*S*=0). As seen in `df_sel_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_sel
```

### Format

A dataframe with 100,000 rows and 5 columns:

**X** exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_sel_source *Data source for* `df_sel`

### Description

Data with complete information on study selection, three known confounders, and 100,000 observations. This data is used to derive `df_sel` and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with `df_sel`. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_sel_source
```

## Format

A dataframe with 100,000 rows and 6 columns:

**X** true exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**S** selection, 1 = selected into the study and 0 = not selected into the study

---

`df_uc` *Simulated data with uncontrolled confounding*

---

## Description

Data containing one source of bias, three known confounders, and 100,000 observations. This data is obtained from `df_uc_source` by removing the column *U*. The resulting data corresponds to what a researcher would see in the real-world: information on known confounders (*C1*, *C2*, and *C3*), but not for confounder *U*. As seen in `df_uc_source`, the true, unbiased exposure-outcome effect estimate = 2.

## Usage

```
df_uc
```

## Format

A dataframe with 100,000 rows and 7 columns:

**X_bi** binary exposure, 1 = present and 0 = absent

**X_cont** continuous exposure

**Y_bi** binary outcome corresponding to exposure *X_bi*, 1 = present and 0 = absent

**Y_cont** continuous outcome corresponding to exposure *X_cont*

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_uc_em — *Simulated data with uncontrolled confounding and exposure misclassification*

### Description

Data containing two sources of bias, three known confounders, and 100,000 observations. This data is obtained from `df_uc_em_source` by removing the columns *X* and *U*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified exposure, *Xstar*, and missing data on a confounder *U*. As seen in `df_uc_em_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_em
```

### Format

A dataframe with 100,000 rows and 5 columns:

**Xstar** misclassified exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_uc_em_sel — *Simulated data with uncontrolled confounding, exposure misclassification, and selection bias*

### Description

Data containing three sources of bias, three known confounders, and 100,000 observations. This data is obtained by sampling with replacement with probability = *S* from `df_uc_em_sel_source` then removing the columns *X*, *U*, and *S*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified exposure, *Xstar*; missing data on a confounder *U*; and missing data for those not selected into the study (*S*=0). As seen in `df_uc_em_sel_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_em_sel
```

### Format

A dataframe with 100,000 rows and 5 columns:

**Xstar** misclassified exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

---

## df_uc_em_sel_source *Data source for* df_uc_em_sel

---

### Description

Data with complete information on the three sources of bias, three known confounders, and 100,000 observations. This data is used to derive `df_uc_em_sel` and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with `df_uc_em_sel`. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3 + \alpha_5 U$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_em_sel_source
```

### Format

A dataframe with 100,000 rows and 8 columns:

**X** true exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**U** unmeasured confounder, 1 = present and 0 = absent

**Xstar** misclassified exposure, 1 = present and 0 = absent

**S** selection, 1 = selected into the study and 0 = not selected into the study

## df_uc_em_source *Data source for* df_uc_em

### Description

Data with complete information on the two sources of bias, a known confounder, and 100,000 observations. This data is used to derive df_uc_em and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with df_uc_em. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 U$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_em_source
```

### Format

A dataframe with 100,000 rows and 7 columns:

**X** true exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**U** unmeasured confounder, 1 = present and 0 = absent

**Xstar** misclassified exposure, 1 = present and 0 = absent

## df_uc_om *Simulated data with uncontrolled confounding and outcome misclassification*

### Description

Data containing two sources of bias, three known confounders, and 100,000 observations. This data is obtained from df_uc_om_source by removing the columns *Y* and *U*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified outcome, *Ystar*, and missing data on the binary confounder *U*. As seen in df_uc_omc_source, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_om
```

### Format

A dataframe with 100,000 rows and 5 columns:

**X** exposure, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

---

`df_uc_om_sel` *Simulated data with uncontrolled confounding, outcome misclassification, and selection bias*

---

### Description

Data containing three sources of bias, three known confounders, and 100,000 observations. This data is obtained by sampling with replacement with probability = *S* from `df_uc_om_sel_source` then removing the columns *Y*, *U*, and *S*. The resulting data corresponds to what a researcher would see in the real-world: a misclassified outcome, *Ystar*; missing data on a confounder *U*; and missing data for those not selected into the study (*S*=0). As seen in `df_uc_om_sel_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_om_sel
```

### Format

A dataframe with 100,000 rows and 5 columns:

**X** exposure, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_uc_om_sel_source *Data source for* df_uc_om_sel

### Description

Data with complete information on the three sources of bias, three known confounders, and 100,000 observations. This data is used to derive df_uc_om_sel and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with df_uc_om_sel. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3 + \alpha_5 U$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_om_sel_source
```

### Format

A dataframe with 100,000 rows and 8 columns:

**X** exposure, 1 = present and 0 = absent

**Y** true outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**U** unmeasured confounder, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

**S** selection, 1 = selected into the study and 0 = not selected into the study

## df_uc_om_source *Data source for* df_uc_om

### Description

Data with complete information on the two sources of bias, three known confounders, and 100,000 observations. This data is used to derive df_uc_om and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with df_uc_om. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 U$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_om_source
```

### Format

A dataframe with 100,000 rows and 7 columns:

**X** exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**U** unmeasured confounder, 1 = present and 0 = absent

**Ystar** misclassified outcome, 1 = present and 0 = absent

---

## df_uc_sel *Simulated data with uncontrolled confounding and selection bias*

---

### Description

Data containing two sources of bias, three known confounders, and 100,000 observations. This data is obtained by sampling with replacement with probability = *S* from `df_uc_sel_source` then removing the columns *U* and *S*. The resulting data corresponds to what a researcher would see in the real-world: missing data on confounder *U*; and missing data for those not selected into the study (*S*=0). As seen in `df_uc_sel_source`, the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_sel
```

### Format

A dataframe with 100,000 rows and 5 columns:

**X** exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

## df_uc_sel_source *Data source for* df_uc_sel

### Description

Data with complete information on the two sources of bias, a known confounder, and 100,000 observations. This data is used to derive df_uc_sel and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with df_uc_sel. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3 + \alpha_5 U$ shows that the true, unbiased exposure-outcome odds ratio = 2.

### Usage

```
df_uc_sel_source
```

### Format

A dataframe with 100,000 rows and 7 columns:

**X** true exposure, 1 = present and 0 = absent

**Y** outcome, 1 = present and 0 = absent

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**U** unmeasured confounder, 1 = present and 0 = absent

**S** selection, 1 = selected into the study and 0 = not selected into the study

## df_uc_source *Data source for* df_uc

### Description

Data with complete information on one source of bias, three known confounders, and 100,000 observations. This data is used to derive df_uc and can be used to obtain bias parameters for purposes of validating the simultaneous multi-bias adjustment method with df_uc. With this source data, the fitted regression $logit(P(Y = 1)) = \alpha_0 + \alpha_1 X + \alpha_2 C1 + \alpha_3 C2 + \alpha_4 C3 + \alpha_5 U$ shows that the true, unbiased exposure-outcome effect estimate = 2 when:

1. g = logit, Y = *Y_bi*, and X = *X_bi* or
2. g = identity, Y = *Y_cont*, X = *X_cont*.

### Usage

```
df_uc_source
```

### Format

A dataframe with 100,000 rows and 8 columns:

**X_bi** binary exposure, 1 = present and 0 = absent

**X_cont** continuous exposure

**Y_bi** binary outcome corresponding to exposure *X_bi*, 1 = present and 0 = absent

**Y_cont** continuous outcome corresponding to exposure *X_cont*

**C1** 1st confounder, 1 = present and 0 = absent

**C2** 2nd confounder, 1 = present and 0 = absent

**C3** 3rd confounder, 1 = present and 0 = absent

**U** uncontrolled confounder, 1 = present and 0 = absent

---

## multibias_adjust *Simultaneously adjust for multiple biases*

---

### Description

`multibias_adjust` returns the exposure-outcome odds ratio and confidence interval, adjusted for one or more biases.

### Usage

```
multibias_adjust(
  data_observed,
  data_validation = NULL,
  bias_params = NULL,
  bootstrap = FALSE,
  bootstrap_reps = 100,
  level = 0.95
)
```

### Arguments

| | |
|---|---|
| `data_observed` | Object of class `data_observed` corresponding to the data to perform bias analysis on. |
| `data_validation` | Object of class `data_validation` corresponding to the validation data used to adjust for bias in the observed data. The validation data should have data for the same variables as in `data_observed`, plus data for the missing variables leading to bias. |
| `bias_params` | Object of class 'bias_params' corresponding to the bias parameters used to adjust for bias in the observed data. There must be parameters corresponding to the bias or biases specified in `data_observed`. |

| | |
|---|---|
| bootstrap | Boolean for whether to perform bootstrapping to obtain the estimate and confidence interval. |
| bootstrap_reps | Integer number of bootstrap samples to run in bootstrapping. |
| level | Value from 0-1 representing the full range of the confidence interval. Default is 0.95. |

## Details

Bias adjustment can be performed by inputting either a validation dataset or the necessary bias parameters. Values for the bias parameters can be applied as fixed values or as single draws from a probability distribution (ex: `rnorm(1, mean = 2, sd = 1)`). The latter has the advantage of allowing the researcher to capture the uncertainty in the bias parameter estimates. To incorporate this uncertainty in the estimate and confidence interval, this function should be run in loop across bootstrap samples of the dataframe for analysis. The estimate and confidence interval would then be obtained from the median and quantiles of the distribution of odds ratio estimates.

## Value

A list including: the bias-adjusted effect estimate of the exposure on the outcome, the standard error, and the confidence interval as the vector: (lower bound, upper bound).

## Examples

```
# Adjust for exposure misclassification -------------------------------------
df_observed <- data_observed(
  data = df_em,
  bias = "em",
  exposure = "Xstar",
  outcome = "Y",
  confounders = "C1"
)

# Using validation data
df_validation <- data_validation(
  data = df_em_source,
  true_exposure = "X",
  true_outcome = "Y",
  confounders = "C1",
  misclassified_exposure = "Xstar"
)

multibias_adjust(
  data_observed = df_observed,
  data_validation = df_validation
)

# Using bias_params
bp <- bias_params(coef_list = list(x = c(-2.10, 1.62, 0.63, 0.35)))

multibias_adjust(
  data_observed = df_observed,
```

```
  bias_params = bp
)

# Adjust for three biases ------------------------------------------------
df_observed <- data_observed(
  data = df_uc_om_sel,
  bias = c("uc", "om", "sel"),
  exposure = "X",
  outcome = "Ystar",
  confounders = c("C1", "C2", "C3")
)

# Using validation data
df_validation <- data_validation(
  data = df_uc_om_sel_source,
  true_exposure = "X",
  true_outcome = "Y",
  confounders = c("C1", "C2", "C3", "U"),
  misclassified_outcome = "Ystar",
  selection = "S"
)

multibias_adjust(
  data_observed = df_observed,
  data_validation = df_validation
)

# Using bias_params
bp1 <- bias_params(
  coef_list = list(
    u = c(-0.32, 0.59, 0.69),
    y = c(-2.85, 0.71, 1.63, 0.40, -0.85, 0.22),
    s = c(0.00, 0.74, 0.19, 0.02, -0.06, 0.02)
  )
)

multibias_adjust(
  data_observed = df_observed,
  bias_params = bp1
)

bp2 <- bias_params(
  coef_list = list(
    u1y0 = c(-0.20, 0.62, 0.01, -0.08, 0.10, -0.15),
    u0y1 = c(-3.28, 0.63, 1.65, 0.42, -0.85, 0.26),
    u1y1 = c(-2.70, 1.22, 1.64, 0.32, -0.77, 0.09),
    s = c(0.00, 0.74, 0.19, 0.02, -0.06, 0.02)
  )
)

# with bootstrapping
## Not run:
multibias_adjust(
```

```
  data_observed = df_observed,
  bias_params = bp2,
  bootstrap = TRUE,
  bootstrap_reps = 1000
)

## End(Not run)
```

---

`multibias_plot` *Create a Forest Plot comparing observed and adjusted effect estimates*

---

## Description

This function generates a forest plot comparing the observed effect estimate with adjusted effect estimates from sensitivity analyses. The plot includes point estimates and confidence intervals for each analysis.

## Usage

```
multibias_plot(data_observed, multibias_result_list, log_scale = FALSE)
```

## Arguments

| | |
|---|---|
| `data_observed` | Object of class `data_observed` representing the observed causal data and effect of interest. |
| `multibias_result_list` | A named list of sensitivity analysis results. Each element should be a result from `multibias_adjust()`. |
| `log_scale` | Boolean indicating whether to display the x-axis on the log scale. Default is FALSE. |

## Value

A ggplot object showing a forest plot with:

- Point estimates (blue dots)
- Confidence intervals (gray horizontal lines)
- A vertical reference line at x=1 (dashed)
- Appropriate labels and title

## Examples

```
## Not run:
df_observed <- data_observed(
  data = df_em,
  bias = "em",
  exposure = "Xstar",
  outcome = "Y",
  confounders = "C1"
)

bp1 <- bias_params(coef_list = list(x = c(-2.10, 1.62, 0.63, 0.35)))
bp2 <- bias_params(coef_list = list(x = c(-2.10 * 2, 1.62 * 2, 0.63 * 2, 0.35 * 2)))

result1 <- multibias_adjust(
  data_observed = df_observed,
  bias_params = bp1
)
result2 <- multibias_adjust(
  data_observed = df_observed,
  bias_params = bp2
)

multibias_plot(
  data_observed = df_observed,
  multibias_result_list = list(
    "Adjusted with bias params" = result1,
    "Adjusted with bias params doubled" = result2
  )
)

## End(Not run)
```

# Index


∗ **datasets**
  df_em, 7
  df_em_om, 8
  df_em_om_source, 8
  df_em_sel, 9
  df_em_sel_source, 10
  df_em_source, 10
  df_om, 11
  df_om_sel, 12
  df_om_sel_source, 12
  df_om_source, 13
  df_sel, 14
  df_sel_source, 14
  df_uc, 15
  df_uc_em, 16
  df_uc_em_sel, 16
  df_uc_em_sel_source, 17
  df_uc_em_source, 18
  df_uc_om, 18
  df_uc_om_sel, 19
  df_uc_om_sel_source, 20
  df_uc_om_source, 20
  df_uc_sel, 21
  df_uc_sel_source, 22
  df_uc_source, 22

bias_params, 3

data_observed, 5
data_validation, 6
df_em, 7
df_em_om, 8
df_em_om_source, 8
df_em_sel, 9
df_em_sel_source, 10
df_em_source, 10
df_om, 11
df_om_sel, 12
df_om_sel_source, 12
df_om_source, 13
df_sel, 14
df_sel_source, 14
df_uc, 15
df_uc_em, 16
df_uc_em_sel, 16
df_uc_em_sel_source, 17
df_uc_em_source, 18
df_uc_om, 18
df_uc_om_sel, 19
df_uc_om_sel_source, 20
df_uc_om_source, 20
df_uc_sel, 21
df_uc_sel_source, 22
df_uc_source, 22

multibias_adjust, 23
multibias_adjust(), *3*, *5*, *26*
multibias_plot, 26